

# Technical specifications for the blasting cabinet



## Technical data

- |                               |                               |
|-------------------------------|-------------------------------|
| • Model                       | <b>CAB 18</b>                 |
| • Power supply                | 240 [VDC] 50Hz                |
| • Inlet air pressure Min/Max  | 2 [bar] / 10 [bar]            |
| • Outlet air pressure Min/Max | 0.5 [bar] / 8.0 [bar]         |
| • Air consumption             | Max 4'000 [l/min]             |
| • Media type                  | <b>All</b>                    |
| • Nozzle type                 | Ø 8mm in Boron Carbide        |
| • Media consumption Min/Max   | 3 [kg/h] / 60 [kg/h]          |
| • Media tank capacity         | 25 kg                         |
| • Total weight                | ~200 kg                       |
| • Larg x Depth x Hight in mm  | 1050 x 1150 x 1675            |
| • Warranty                    | <b>2 years or 1'000 hours</b> |

**SICT-Blasting**

Tél: +41(0)21-802 53 00

[www.sict-blasting.com](http://www.sict-blasting.com)

# Specifications

## Details

- Painted steel frame
- Power on by activating the control pedal and power off after 30 seconds of no activity
- Control of blasting or blowing application by pressing the control pedal
- Air or air-media switch button on the front panel of the cabinet
- Blasting hose of Ø 19mm (inside diameter)
- Air filter obstruction indicator on the front panel of the cabinet
- Automatic cleaning system of the filter by compressed air source
- « STOP » button on the front panel of the cabinet
- Left side door 420mm x 420mm with positive security
- Working table Ø 400mm with side way rails and rotating option, can support 50kg maxi
- Integrated dust control system with TWO filtering cartridge in the back
- Bottom grid in the blasting room to evacuate the aggregate
- 2 blasting sleeves (without gloves) on the front of the cabinet
- Working window 460mm x 200mm
- Electrical motor of the fan is 220V - 370W

**SICT-Blasting**

Tél: +41(0)21-802 53 00

**[www.sict-blasting.com](http://www.sict-blasting.com)**